

Ordering a Lead Screw Assembly

Part Number Configuration Guide



KTA 025062 - RA / 1K / 4N / 6.00 / TS

Nut Code _____
See table to the right

Screw Code _____
See tables on pages 27-41

Helix Direction _____
R = Right Hand Thread
L = Left Hand Thread

Material _____
A = Alloy Steel, Rolled
S = Stainless Steel, Rolled

First End Configuration
End Type _____
Type 1, 2, 3, 4

Shaft Extension _____
K = With Keyway
L = Without Keyway
N = No Shaft Extension


Second End Configuration
End Type _____
Type 1, 2, 3, 4

Shaft Extension _____
K = With Keyway
L = Without Keyway
N = No Shaft Extension

Overall Length (OAL) _____
In inches, to two decimal places. "00" if ordering nut only

Modifier List _____
S or M Required

S = Standard
M = Modified
F = Round Flange
T = PTFE Coating



Nut Codes

Code	Description
NTA	Standard Freewheeling Threaded
NFA	Standard Freewheeling Flanged
ATA	Axial Anti-Backlash Threaded
AFA	Axial Anti-Backlash Flanged
RTA	Radial Anti-Backlash Threaded
RFA	Radial Anti-Backlash Flanged
KTA	Torsional Anti-Backlash Threaded
KFA	Torsional Anti-Backlash Flanged
GTD	Compact Torsional Anti-Backlash Threaded
GFD	Compact Torsional Anti-Backlash Flanged
BNR	Ball Nut Replacement
TMA	Plastic Trunnion Mounting Nut
TMB	Bronze Trunnion Mounting Nut
HLC	Heavy Load Nut Compact Flanged
HLR	Heavy Load Nut Round Flanged
SNA	Sleeve Nut (GP Acetal)
SNB	Sleeve Nut Bronze
HAFA	Hurricane Axial Anti-Backlash Flanged
HNFA	Hurricane Freewheeling Standard Flanged
NPA	Acme Plastic Threaded
NPB	Acme Bronze Threaded